### HYDRG-SPRAY

# WATER SOFTENERS



FREEDOM SERIES

PATRIOT SERIES

#### Hydro-Spray Water Softeners

High quality water is essential at the car wash to produce consistent results and a quality wash. Soft water will lower your chemical usage reducing cost per vehicle washed 10% or more, while enhancing the foaming characteristics of your detergents. Soft Water improves the efficiency of your RO System and extends the life of expensive RO Membrane Filters. Water Softeners remove hardness/Iron and other containments commonly found in fresh water that cause scaling inside water lines and pumping systems or even plugged nozzles. It's recommended that a water sample be taken from the location and sent into Hydro-Spray for proper testing to determine what equipment is right for your car wash!

### HYDRG-SPRAY

## WATER SOFTENERS

Model 1'			Dim (L"xW"H")
DCS7-60-100	60,000/50,000	16/24	56x18x61
DCS7-90-100	90,000/75,000	18/28	65x24x74
DCS7-180-100	180,000/150,000	20/28	77x24x71

876. G/G/C/2		Flow Rate	Dim
Model <i>1.25</i> '	Capacity (Max/Min)	(Cont/ Peak)	(L"xW"H")
DCS6-90-125	90,000/72,000	23/32	44x24x73
DCS6-120-125	120,000/96,000	25/34	46x24x73
DCS6-150-125	150,000/120,000	26/35	72x24x73

		Flow Rate	Dim
Model <i>1.5</i> '	Capacity (Max/Min)	(Cont/ Peak)	(L"xW"H")
DCS6-90-150	90,000/72,000	36/54	64x24x75
DCS6-150-150	150,000/120,000	46/64	72x24x75
DCS6-210-150	210,000/168,000	50/69	78x24x72

18 44 43		1434-1437	Flow Rate	Dim
Model	2'	Capacity (Max/Min)	(Cont/ Peak)	(L"xW"H")
DCS6-150-2	200	150,000/120,000	59/89	72x24x73
DCS6-210-2	200	210,000/168,000	69/100	78x24x70
DCS6-300-2	200	300,000/240,000	75/105	90x30x80



#### Freedom 1" and Patriot 1.25" Water Softeners

- Up to 28 gpm Continuous & 37 gpm Peak Flow Rates
- Corrosion Resistant Norell Control Valve Body
- **Integrated Flow Meter**
- Fully Programmable Regeneration Settings
- Turn-key System
- Bypass Assembly Included



#### Patriot 1.5" or 2" Water Softeners

- Up to 99 gpm Continuous & 130 gpm Peak Flow Rates
- Epoxy Coated Lead-Free Brass Valve Body and Stainless Steel Flow Meter
- Fully Programmable Regeneration Settings

Concerned about costly delays and expensive plumber bills during the installation of your twin water softener Let us take care of it for you with a custom - built pre-plumbed copper header. All you have to do is connect the common inlet, outlet, drain and you are ready to start it up!

